




Punches & Dies

DESIGNER LINE > Guides

- Hole Tolerance +.0002 -.0000
- A2 Tool Steel*
- Hardened and drawn to RC 60-63
- Concentricity .0003 T.I.R.(Round or Shaped)



Dimensions shown are catalog guidelines-exceptions available at additional cost

*Other Steels available upon request at additional cost

Straight Type Catalog Information										
Body Code	Body Dia +.0002 +.0004	Round		Oblong		Rectangular		Blanks		Length
		Cat. No.	P Range +.0002 -.0000	Cat. No.	P Max	Cat. No.	Max Diag.	+.0002	+.0004	
1A	.1875	DPG1A	.062-.128	--	--	--	--	--	--	.50 .62 --
2	.2500	DPG2	.062-.170	DPGO2	.170	DPGR2	.170	DPGR2		.50 .62 .75
2A	.3125	DPG2A	.093-.212	DPGO2A	.212	DPGR2A	.212	DPGR2A		.50 .62 .75
3	.3750	DPG3	.125-.255	DPGO3	.255	DPGR3	.255	DPGR3		.50 .62 .75
3A	.4375	DPG3A	.187-.297	DPGO3A	.297	DPGR3A	.297	DPGR3A		.50 .62 .75
4	.5000	DPG4	.212-.344	DPGO4	.344	DPGR4	.344	DPGR4		.50 .62 .75
5	.6250	DPG5	.293-.425	DPGO5	.425	DPGR5	.425	DPGR5		.50 .62 .75

Head Type Catalog Information											
	Body Dia +.0002 +.0004	Round		Oblong		Rectangular		Blanks		Length	Head Dia
		Cat. No.	P Range +.0002 -.0000	Cat. No.	P Max	Cat. No.	Max Diag.	+.0002	+.0004		
1A	.1875	DHG1A	.062-.128	--	--	--	--	--	--	.50 .62 .75	.312
2	.2500	DHG2	.062-.170	DHGO2	.170	DHGR2	.170	DHGB2		.50 .62 .75	.375
2A	.3125	DHG2A	.093-.212	DHGO2A	.212	DHGR2A	.212	DHGB2A		.50 .62 .75	.437
3	.3750	DHG3	.125-.255	DHGO3	.255	DHGR3	.255	DHGB3		.50 .62 .75	.500
3A	.4375	DHG3A	.187-.297	DHGO3A	.297	DHGR3A	.297	DHGB3A		.50 .62 .75	.562
4	.5000	DHG4	.212-.344	DHGO4	.344	DHGR4	.344	DHGB4		.50 .62 .75	.625
5	.6250	DHG5	.293-.425	DHGO5	.425	DHGR5	.425	DHGB5		.50 .62 .75	.750