




Punches & Dies

BALL LOCK PUNCHES & RETAINER SETS > Punches > Oblong Punch

- Available in M2 Tool Steel*
- Hardened and drawn to RC 60-63. Heads redrawn to RC 40-55.
- Concentricity .0005 T.I.R.(Round) .001 T.I.R. (Shaped)

Dimensions shown are catalog guidelines-exceptions available at additional cost

*Other Steels available upon request at additional cost



Light Duty Oblong Catalog Information

Body Diameter	Point Length	Cat. No.	W Min +.0005 -.0005
2 .2500	.50	BPO2	.062
3 .375	.62	BPO3	.125
4 .5000	.75	BPO4	.125
5 .625	.87	BPO5	.187
6 .750	.93	BPO6	.250
7 .875	.93	BPO7	.375
8 1.000	.93	BPO8	.437

Heavy Duty Oblong Catalog Information

Body Diameter	Point Length	Cat. No.	W Min +.0005 -.0005
2 .2500	.50	BXPO2	.062
3 .375	.62	BXPO3	.125
4 .5000	.75	BXPO4	.125
5 .625	.87	BXPO5	.187
6 .750	.93	BXPO6	.250
7 .875	.93	BXPO7	.375
8 1.000	.93	BXPO8	.437