




Punches & Dies

STANDARD LINE > Dies > Straight Type > Rectangle Dies

- A2 Tool Steel*
- Hardened and drawn to RC 60-63
- Concentricity .0005 T.I.R.(Round) .001 T.I.R. (Shaped)



Dimensions shown are catalog guidelines-exceptions available at additional cost

*Other Steels available upon request at additional cost

Straight Type Rectangle												
Body Diameter	Point Length	Cat. No.	W Min. +.0005 -.0005	Max Diag.	Lengths						Max. C'Bore Dia.	Min. Land Lgth.
1A	.1875				.50	.75	.88	1.00	1.12	1.25	.17	.09
2	.2500				.50	.75	.88	1.00	1.12	1.25	.17	.15
3	.3750	PDR3	.048	.195	.50	.75	.88	1.00	1.12	1.25	.24	.15
4	.5000	PDR4	.064	.285	.50	.75	.88	1.00	1.12	1.25	.32	.18
5	.6250	PDR5	.095	.365	.50	.75	.88	1.00	1.12	1.25	.39	.18
6	.7500	PDR6	.127	.435	.50	.75	.88	1.00	1.12	1.25	.48	.18
7	.8750	PDR7	.158	.545	.50	.75	.88	1.00	1.12	1.25	.59	.25
8	1.000	PDR8	.189	.675	.50	.75	.88	1.00	1.12	1.25	.70	.25
10	1.2500	PDR10	.220	.800	.50	.75	.88	1.00	1.12	1.25	.82	.25
12	1.5000	PDR12	.252	1.050	.50	.75	.88	1.00	1.12	1.25	1.08	.31

*1.50 length available upon request