




Punches & Dies

STANDARD LINE > Punches > Oblong Ejector

- Available in M2 or A2 Tool Steel*
- Hardened and drawn to RC 60-63. Heads redrawn to RC 40-55.
- Concentricity .0005 T.I.R.(Round) .001 T.I.R. (Shaped)



Dimensions shown are catalog guidelines-exceptions available at additional cost

*Other Steels available upon request at additional cost

Oblong Ejector Punches Catalog Information

Body Diameter	Point Length	Cat. No.	W Min +.0005 -.0005
1 .1250	.12	--	---
	.25	--	--
	.50	--	--
1A .1875	.12	HEO1A	.062
	.25	HEOM1A	.062
	.50	--	--
2 .2500	.25	HEO2	.062
	.37	HEOM2	.093
	.50	HEOL2	.093
2A .3125	.31	HEO2A	.093
	.50	HEOM2A	.125
	.75	HEOL2A	.125
3 .375	.37	HEO3	.125
	.75	HEOM3	.187
	1.00	HEOL3	.187
3A .4375	.43	HEO3A	.125
	.75	HEOM3A	.187
	1.00	HEOL3A	.187
4 .5000	.50	HEO4	.125
	.75	HEOM4	.250
	1.00	HEOL4	.250
5 .625	.62	HEO5	.187
	1.00	HEOM5	.281
	1.25	--	--
6 .750	.75	HEO6	.250
	1.00	HEOM6	.312
	1.25	--	--
8 1.000	1.00	HEO8	.375
	1.25	--	--
	1.50	--	--