



Punches & Dies

STANDARD LINE > Punches > Rectangle Ejector

- Available in M2 or A2 Tool Steel*
- Hardened and drawn to RC 60-63. Heads redrawn to RC 40-55.
- Concentricity .0005 T.I.R.(Round) .001 T.I.R. (Shaped)

Dimensions shown are catalog guidelines-exceptions available at additional cost

*Other Steels available upon request at additional cost

Rectangle Ejector Punches Catalog Information

Body Diameter	Point Length	Cat. No.	W Min +.0005 -.0005
1 .1250	.12	--	---
	.25	--	--
	.50	--	--
1A .1875	.12	HER1A	.062
	.25	HERM1A	.062
	.50	--	--
2 .2500	.25	HER2	.062
	.37	HERM2	.093
	.50	HERL2	.093
2A .3125	.31	HER2A	.093
	.50	HERM2A	.125
	.75	HERL2A	.125
3 .375	.37	HER3	.093
	.75	HERM3	.187
	1.00	HERL3	.187
3A .4375	.43	HER3A	.125
	.75	HERM3A	.187
	1.00	HERL3A	.187
4 .5000	.50	HER4	.125
	.75	HERM4	.250
	1.00	HERL4	.250
5 .625	.62	HER5	.187
	1.00	HERM5	.281
	1.25	--	--
6 .750	.75	HER6	.250
	1.00	HERM6	.312
	1.25	--	--
8 1.000	1.00	HER8	.375
	1.25	--	--
	1.50	--	--