



# Punches & Dies

## STANDARD LINE > Punches > Rectangle Punches

- Available in M2 or A2 Tool Steel\*
- Hardened and drawn to RC 60-63. Heads redrawn to RC 40-55.
- Concentricity .0005 T.I.R.(Round) .001 T.I.R. (Shaped)



Dimensions shown are catalog guidelines-exceptions available at additional cost

\*Other Steels available upon request at additional cost

Rectangle Punches Catalog Information

Body Diameter	Point Length	Cat. No.	W Min +.0005 -.0005
1 .1250	.12	HPR1	.050
	.25	HPRM1	.062
	.50	HPRL1	.062
1A .1875	.12	HPR1A	.050
	.25	HPRM1A	.062
	.50	HPRL1A	.062
2 .2500	.25	HPR2	.062
	.37	HPRM2	.062
	.50	HPRL2	.062
2A .3125	.31	HPR2A	.093
	.50	HPRM2A	.093
	.75	HPRL2A	.093
3 .375	.37	HPR3	.093
	.75	HPRM3	.125
	1.00	HPRL3	.125
3A .4375	.43	HPR3A	.125
	.75	HPRM3A	.187
	1.00	HPRL3A	.187
4 .5000	.50	HPR4	.125
	.75	HPRM4	.187
	1.00	HPRL4	.187
5 .625	.62	HPR5	.187
	1.00	HPRM5	.250
	1.25	HPRL5	.250
6 .750	.75	HPR6	.250
	1.00	HPRM6	.312
	1.25	HPRL6	.312
8 1.000	1.00	HPR8	.375
	1.25	HPRM8	.400
	1.50	HPRL8	.400